

BASIC TYPE - **SENSING DISPLACER** - **INSERTION DISTANCE** - **PROCESS CONNECTION** - **SWITCH AND HOUSING** - **OPTIONS**

MODEL
EXAMPLE: 718A - 23Y - 30' - 3"150RS - S1W - AA

BASIC TYPE

M/N	DESCRIPTION
718A	4 STATION 4 DISPLACER

316 S.S. SPRING: 250°F MAXIMUM;
INCONEL SPRING TO 450°F
BASIC: 316 S.S. TRIM,
416 S.S. ATTRACTOR

INSERTION DISTANCE

M/N	DESCRIPTION
10	10 FT OF 316 S.S. CABLE
#	UP TO 50 FEET OF 316 S.S. CABLE, MAXIMUM

REPLACE "#" WITH REQ'D FEET OF CABLE.
FOR MONEL OR HASTELLOY "C" CABLE: C/F

PROCESS CONNECTION

M/N	PROCESS CONNECTIONS
3" NPT*	3" NPT
3" 150R*	3" 150# ANSI FLANGE
3" 300R*	3" 300# ANSI FLANGE
3" 600R*	3" 600# ANSI FLANGE
4" 150R*	4" 150# ANSI FLANGE
4" 300R*	4" 300# ANSI FLANGE

REPLACE "*" WITH "S" FOR STEEL,
"B" FOR 304 S.S., OR
"Y" FOR 316 S.S.
CONSULT FACTORY FOR OTHER SIZES &
RATINGS.

SENSING DISPLACER

DISPLACERS (INCHES)						WKG PSIG @ °F			MINIMUM ANSI FLANGED	
M/N	MAT *	MIN SPG	MAX SPG	O.D.	LENGTHS	100°F	250°F	400°F	NPT	NOZZLE
84Y	316 S.S.	0.45	0.51	3.5	10,12.5,12.5,12.5	385	300	250	N/A	4" SCH 80
85Y	316 S.S.	0.48	0.54	3.5	10,12.5,12.5,12.5	385	300	250	N/A	4" SCH 80
86Y	316 S.S.	0.50	0.57	3.5	8.1,10,10,12.5	385	300	250	N/A	4" SCH 80
87Y	316 S.S.	0.55	0.64	3.5	8.1,10,10,12.5	385	300	250	N/A	4" SCH 80
88Y	316 S.S.	0.60	0.70	3.5	5.9,8.1,8.1,10	385	300	250	N/A	4" SCH 80
89Y	316 S.S.	0.65	0.76	3.5	5.9,8.1,8.1,10	385	300	250	N/A	4" SCH 80
20Y	316 S.S.	0.70	0.82	3.5	5.9,8.1,8.1,10	385	300	250	N/A	4" SCH 80
21Y	316 S.S.	0.75	0.85	2.9	7.1,10,10,12	500	400	325	3"	3" SCH 80
22Y	316 S.S.	0.80	0.94	2.9	7.1,10,10,12	500	400	325	3"	3" SCH 80
23Y	316 S.S.	0.90	1.06	2.9	7.1,10,10,12	500	400	325	3"	3" SCH 80
25Y	316 S.S.	1.01	1.20	2.9	5.9,8.2,8.1,10	500	400	325	3"	3" SCH 80
26Y	316 S.S.	1.10	1.30	2.9	5.9,8.2,8.2,10	500	400	325	3"	3" SCH 80
27Y	316 S.S.	1.20	1.40	2.9	4.8,7.1,7.1,8.2	500	400	325	3"	3" SCH 80
28Y	316 S.S.	1.30	1.50	2.9	4.8,7.1,7.1,8.2	500	400	325	3"	3" SCH 80
29Y	316 S.S.	1.40	1.65	2.9	4.8,7.1,7.1,8.2	500	400	325	3"	3" SCH 80

* 316 S.S. ALSO AVAILABLE IN SOLID POLYPROPYLENE; WORKING PRESSURE OF 2200 PSIG @ 100°F; LIMITED TO 1520 PSIG @ 220°F MAXIMUM. CHANGE "Y" TO "P"

SWITCH AND HOUSING

M/N FIRST CHARACTER	SWITCH TYPE - SERVICE AND LOAD RATINGS
S	GENERAL USE, COMPACT, 4 AMP @ 28VDC, 5 AMP @ 125VAC, 250VAC -65 to 250°F (-54 to 121°C)
M/N SECOND CHARACTER	NUMBER OF CONTACTS
1	1 SPDT CONTACT
2	2 SPDT CONTACTS
M/N THIRD CHARACTER	HOUSING RATING
W	Type 4X, IP65
X	TYPE 4X, IP65 (EPOXY COATED)
C	ALUMINUM - FOR HAZARDOUS LOCATIONS; SEE CSA RATINGS
T	300 STAINLESS STEEL - FOR HAZARDOUS LOCATIONS; SEE CSA RATINGS

OPTIONS

M/N	DESCRIPTION
AA	NONE
IN	INCONEL SPRING 450°F INCREASE MIN. SPG BY 6%
SA	316 S.S. SHEATHED ATTRACTOR
HH	120VAC ELECTRICAL HOUSING HEATER TO PREVENT CONDENSATION & ICING



CSA Ratings:
Housing types 'C' and 'T'
Cl I Div 1, Gr B,C,D; Cl II, Div 1 Gr E,F,G; CL III Div 1
Class I Zone 1, Ex/AEx d IIB+H₂
Maximum contact ratings 250Vac, 5A, T5 with max
ambient 80°C. T6 without heater with max ambient 60°C



585 Fortson Street
Shreveport, La. 71107 - USA
P: +1(318) 424-8471
F: +1(318) 425-2421
sales@deltacnt.com
www.deltacnt.com